

Control Cable

PVC Insulated and Sheathed Flexible Control Cables



No. Of Cores X Cores Section	Max. Dia Of Conductor Strands	Thickness of Insulation Nominal	Finished Cable Dia Nominal	Approx. Net weight	Max. Electrical Resistance at 20°C
Sq mm	mm	mm	mm	kg/km	ohms/km
5 x 1.5	0.2	0.6	8.2	86.0	13.3
6 x 1.5	0.2	0.6	8.9	99.5	13.3
7 x 1.5	0.2	0.6	9.8	118.6	13.3
8 x 1.5	0.2	0.6	10.6	137.0	13.3
10 x 1.5	0.2	0.6	11.7	164.7	13.3
12 x 1.5	0.2	0.6	12.1	175.5	13.3
14 x 1.5	0.2	0.6	12.9	198.1	13.3
16 x 1.5	0.2	0.6	13.6	219.1	13.3
18 x 1.5	0.2	0.6	14.5	247.7	13.3
20 x 1.5	0.2	0.6	15.2	271.2	13.3
24 x 1.5	0.2	0.6	19.0	360.2	13.3
27 x 1.5	0.2	0.6	20.2	418.1	13.3
37 x 1.5	0.2	0.6	25.3	471.2	13.3
61 x 1.5	0.2	0.6	10.2	733.6	13.3
5 x 2.5	0.2	0.6	12.0	137.6	7.98
6 x 2.5	0.2	0.6	12.1	182.8	7.98
7 x 2.5	0.2	0.6	13.2	185.5	7.98
8 x 2.5	0.2	0.6	15.1	217.0	7.98
10 x 2.5	0.2	0.6	15.2	277.7	7.98
12 x 2.5	0.2	0.6	16.1	281.2	7.98
14 x 2.5	0.2	0.6	16.8	313.0	7.98
16 x 2.5	0.2	0.6	18.1	393.0	7.98
18 x 2.5	0.2	0.6	18.2	390.3	7.98
20 x 2.5	0.2	0.6	20.7	394.4	7.98
24 x 2.5	0.2	0.6	19.5	504.4	7.98
27 x 2.5	0.2	0.6	21.2	528.0	7.98
37 x 2.5	0.2	0.6	23.5	644.3	7.98
61 x 2.5	0.2	0.6	32.0	1177.5	7.98