




Compression Terminal Copper Long Barrel Two Hole (AWG)

- ETP copper alloy c11000 per ASTM SPEC B188 copper tube
- Electro tinned plated



Product Ref.	Conductor Size	Colour Code	Dimensions inches						
			O	I	B	W	T	C	L
CAT 1000-3	1000 MCM	WHITE	1.504	1.170	2.94	2.16	0.32	3.00	6.84
CAT 750 -3	750 MCM	BLACK	1.302	1.030	2.81	1.88	0.27	3.00	6.46
CAT 600 -3	600 MCM	GREEN	1.185	0.920	2.83	1.71	0.27	3.00	6.20
CAT 500 -3	500 MCM	BROWN	1.064	0.830	2.19	1.53	0.23	3.00	5.74
CAT 350 -3	350 MCM	RED	0.877	0.700	1.94	1.27	0.18	3.00	5.44
CAT 300 -3	300 STR	WHITE	0.815	0.649	2.00	1.18	0.16	3.00	5.44
CAT 250 -3	250 STR	YELLOW	0.753	0.594	1.83	1.09	0.16	3.00	5.04
CAT 4/0 -3	4 / 0 STR	PURPLE	0.691	0.545	1.83	1.00	0.14	3.00	5.00
CAT 3/0 -3	3 / 0 STR	ORANGE	0.618	0.487	1.50	0.90	0.12	3.00	4.84
CAT 2/0 -3	2 / 0 STR	BLACK	0.583	0.448	1.53	0.82	0.12	3.00	4.84
CAT 1/0 -3	1 / 0 STR	PINK	0.515	0.391	1.41	0.75	0.12	3.00	4.66
CAT 1 -3	1 STR	GREEN	0.462	0.354	1.41	0.80	0.09	3.00	4.66
CAT 2 -3	2 STR	BROWN	0.418	0.307	1.28	0.82	0.11	3.00	4.52
CAT 3 -3	3 STR	WHITE	0.371	0.289	1.22	0.83	0.11	3.00	4.44
CAT 4 -3	4 STR	GRAY	0.340	0.248	1.18	0.83	0.11	3.00	4.38

Copper Butt Splices Short Barrel (AWG)



- ETP copper alloy c11000 per ASTM SPEC B188 copper tube
- Electro tinned plated



Product Ref.	Conductor Size	Colour Code	Die Index	Dimensions inches		
				O	I	L
CAS 1000-1	1000 MCM	WHITE	27	1.504	1.170	4.28
CAS 750 -1	750 MCM	BLACK	24	1.302	1.030	3.75
CAS 600 -1	600 MCM	GREEN	22 OR 472	1.185	0.920	3.25
CAS 500 -1	500 MCM	BROWN	20 OR 299	1.064	0.830	3.15
CAS 400 -1	400 MCM	BLUE	19 OR 470	0.953	0.758	2.75
CAS 350 -1	350 MCM	RED	18 OR 324	0.877	0.700	2.62
CAS 300 -1	300 MCM	WHITE	17 OR 298	0.815	0.649	2.50
CAS 250 -1	250 MCM	YELLOW	16	0.753	0.594	2.50
CAS 4/0 -1	4 / 0 STR	PURPLE	15	0.691	0.545	2.32
CAS 3/0 -1	3 / 0 STR	ORANGE	14	0.618	0.487	2.32
CAS 2/0 -1	2 / 0 STR	BLACK	13	0.563	0.446	2.18
CAS 1/0 -1	1 / 0 STR	PINK	12 OR 348	0.515	0.391	2.09
CAS 1 -1	1 STR	GREEN	11 OR 375	0.462	0.354	2.09
CAS 2 -1	2 STR	BROWN	10	0.416	0.307	2.09
CAS 3 -1	3 STR	WHITE	9	0.377	0.284	2.09
CAT 4 -1	4 STR	GRAY	8 OR 346	0.340	0.248	2.00
CAT 6 -1	6 STR	BLUE	7 OR 374	0.292	0.195	1.75