


Aluminum Forged Lugs DIN: 48201

- Electrolytic high conductivity aluminum
- Electro tinned plated



Product Ref.	Conductor Size mm²	Stud Hole	Dimensions mm				
			E	I	O	L	W
CAL-16/8	16	M 8	5.4	12	50.0	20	
CAL-16/10		M 10					
CAL-25/8		M 8					20
CAL-25/10	25	M 10	6.8	12	50.0	25	
CAL-25/12		M 12					25
CAL-35/8		M 8					
CAL-35/10	35	M 10	8.0	14	62.0	25	
CAL-35/12		M 12					
CAL-50/8		M 8					
CAL-50/10	50	M 10	9.8	16	62.0	25	
CAL-50/12		M 12					
CAL-70/8		M 8					
CAL-70/10	70	M 10	11.2	18	72.0	25	
CAL-70/12		M 12					
CAL-95/8		M 8					
CAL-95/10	95	M 10	13.2	22	75	25	25
CAL-95/12		M 12			75	25	25
CAL-95/16		M 16			80	30	30
CAL-120/10		M 10					
CAL-120/12	120	M 12	14.7	22	80	30	
CAL-120/16		M 16					
CAL-150/10		M 10					
CAL-150/12	150	M 12	16.3	25	90	30	
CAL-150/16		M 16					
CAL-185/10		M 10					
CAL-185/12	185	M 12	18.3	28	91	30	
CAL-185/16		M 16					
CAL-240/12		M 12					
CAL-240/16	240	M 16	21.0	32	103	38	
CAL-240/20		M 20					
CAL-300/12		M 12					
CAL-300/16	300	M 16	23.3	34	103	38	
CAL-300/20		M 20					
CAL-400/12		M 12					
CAL-400/16	400	M 16	26.0	38	116	38	
CAL-400/20		M 20					
CAL-500/12		M 12					
CAL-500/16	500	M 16	29.0	44	122	44	
CAL-500/20		M 20					
CAL-400A/16		M 16	28.0	42	116	38	
CAL-400A/20	400	M 20					
CAL-500A/16		M 16	31.0	46	122	44	
CAL-500A/20		M 20					