


Copper Fork Hook Terminal End

For Solderless Crimping to Copper/Aluminum Conductor

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm²	Stud Hole E	Dimensions mm									
			I	O	W	T	B	K	C2	P	L-1	L
CFH-7279	0.75	2.3	0.9	2.9	4.0	0.5	3	-	5	1.2	8	11
CFH-7278	1.5	2.3	1.6	3.2	5.0	0.8	5	-	5.2	1.0	10.2	13
CFH-7265	1.5	2.3	1.6	3.2	4.5	0.8	5	-	5.2	1.0	10.2	13
CFH-7266	1.5	4.1	1.7	3.3	7.5	0.8	5	-	6.5	2.4	11.5	15
CFH-7256	1.5	3.6	1.6	3.2	6.8	0.8	5	2	3	1.6	10	15
CFH-7257	1.5	5.1	1.6	3.2	8.0	0.8	5	2	5	1.6	12	18
CFH-7270	1.5	6.3	1.6	3.2	12.0	0.8	5	3	5	1.6	13	19
CFH-7271	1.5	8.1	1.6	3.2	12.0	0.8	5	3	5	1.6	13	19
CFH-7258	2.5	3.6	2.3	3.9	6.5	0.8	5	2	3	1.6	10	15
CFH-7259	2.5	4.1	2.3	3.9	7.7	0.8	5	2	3	1.6	10	16
CFH-7260	2.5	5.1	2.3	3.9	10.0	0.8	5	2	5	1.6	12	18
CFH-7272	2.5	6.3	2.3	3.9	12.0	0.8	5	3	5	1.6	13	19
CFH-7273	2.5	8.1	2.3	3.9	12.0	0.8	5	3	5	1.6	13	19
CFH-7274	4.0	4.1	3.1	5.5	10.0	1.2	6	3	5	2.0	14	20
CFH-7275	4.0	5.1	3.1	5.5	10.0	1.2	6	3	5	2.0	14	20
CFH-7276	4.0	6.3	3.1	5.5	12.0	1.2	6	3	5	2.0	14	20
CFH-7277	4.0	8.1	3.1	5.5	12.0	1.2	6	3	5	2.0	14	20
CFH-7261	4-6	4.1	3.5	5.5	10.0	1.0	6	3	3	2.0	12	18
CFH-7262	4-6	5.1	3.5	5.5	10.0	1.0	6	3	5	2.0	14	20
CFH-7263	4-6	5.1	3.5	5.5	12.0	1.0	6	3	5	2.0	14	20
CFH-7268	4-6	4.1	3.5	5.5	8.0	1.0	6	2	5	2.0	13	17
CFH-7269	4-6	5.1	3.5	5.5	8.0	1.0	6	2	5	2.0	13	17
CFH-7264	6.0	4.1	3.9	5.9	10.0	1.0	6	4	3	2.0	13	19
CFH-7267	6.0	4.1	3.9	5.9	10.0	1.0	6	-	8.5	1.5	14.5	20.5