

## Cable Glands: Type PG

## **Application:**

In outdoor or indoor areas with armoured braided unarmoured or lead sheathed unarmoured cable where it is essential to produce ip55 seal on the inner sheath.

## Function:

Size

Offer a dustproof seal on to the outer sheath of an armoured, braided or armoured cable.

Standard : As per german standard Mechanical : Impact resistant.

: PG - 9 to PG - 48 Material : Brass. **Finish** : Nickel

Gasket : Neoprene (Onion type)

|  | Ī        |
|--|----------|
|  | <u>\</u> |



| SIZE     | THREAD | CABLE   | HEXAGONAL |      |
|----------|--------|---------|-----------|------|
|          | LENGTH | MAXIMUM | DETAILS   |      |
|          | 'D'    | MAX 'A' | A/F       | A/C  |
| PG- 7    | 8      | 9       | 15        | 17.5 |
| PG- 9    | 8      | 12      | 18        | 20   |
| PG- 11   | 8      | 15      | 22        | 23   |
| PG- 13.5 | 10     | 16      | 24        | 26   |
| PG- 16   | 10     | 18      | 25        | 27   |
| PG- 21   | 10     | 24      | 30        | 33   |
| PG- 29   | 10     | 32      | 42        | 48   |
| PG- 36   | 12     | 42      | 50.5      | 58.5 |
| PG- 42   | 12     | 47.5    | 60        | 66   |
| PG- 48   | 15     | 52      | 67        | 73.5 |